

MODULAR COUNTERS

CARIBBEAN REFRIGERATED CONTACT COOLED ISLAND WELL

MODEL NO: CARIB1.3

Designed to achieve a deck temperature of 0°C to 1°C in temperatures not exceeding 32°C.



DIMENSIONS

CARIB1.312: 1206mm x 700mm x 900mm

Well: 1010mm x 580mm x 100mm

CARIB1.316: 1606mm x 700mm x 900mm

Well: 1310mm x 580mm x 100mm

CARIB1.319: 1906mm x 700mm x 900mm

Well: 1610mm x 580mm x 100mm

ELECTRICAL CONNECTIONS

220V/240V; 1 phase 50Hz

1206 model: 1.5kW loading

1606 model: 1.5kW loading

1906 model: 1.5kW loading

Cable: 2 metres with 13 amp plug fitted

CONSTRUCTION

Top: Stainless steel

Exterior: Colour plastic coated steel or stainless steel

Well: Stainless steel

CAPACITY

1206 model: 3 x GN1/1 x 100mm deep

1606 model: 4 x GN1/1 x 100mm deep

1906 model: 5 x GN1/1 x 100mm deep

PRODUCT FEATURES

- Slide out refrigeration modules for ease of maintenance
- One piece 304 grade stainless steel well radiused to base for ease of cleaning
- Automatic defrost & condense handling system
- 1.5mm stainless steel tops with radius front & rear
- Four x 100mm swivel castors two braked
- 14 different colour coated steel finish options

EXTRAS

- Alternative gantries & overshelves
- Tray rails
- Corner bumpers
- Push bar
- Height adjustable feet instead of castors

REFRIGERANT

R452a - zero ODP and low GWP refrigerant

OPERATING CONDITIONS

Well Base temperature 0°C to +1°C up to maximum ambient of +32°C RH 60%



VICTOR

TELEPHONE
01274 722125

EMAIL
sales@victormfg.co.uk

WEBSITE
www.victoronline.co.uk