

MODULAR COUNTERS

CARIBBEAN REFRIGERATED DELI COUNTERS

MODEL NO: CARIB72.9

Caribbean refrigerated blown air wells are part of the most versatile range of standard modular counter in the market place. They provide the basis for all types of counter layouts in different finishes to suit any location. The versatility of Caribbean counters allow its use across all market sectors.



DIMENSIONS

CARIB72.912: 1206mm x 777mm x 900mm

Well: 975mm x 530mm x 170mm

CARIB72.916: 1606mm x 777mm x 900mm

Well: 1305mm 530mm x 170mm

CARIB72.919: 1906mm x 777mm x 900mm

Well: 1635mm x 530mm x 170mm

ELECTRICAL CONNECTIONS

220V/240V; 1 phase 50Hz

1206 model: 1.6kW loading

1606 model: 2.1kW loading

1906 model: 2.4kW loading

CONSTRUCTION

Top: Stainless steel

Exterior: Colour plastic coated steel or stainless steel

Interior: Stainless steel

CAPACITY

1206 model: 3 x GN1/1 x 100mm deep

1606 model: 4 x GN1/1 x 100mm deep

1906 model: 5 x GN1/1 x 100mm deep

PRODUCT FEATURES

- 304 Stainless steel well - 170mm deep
- Load line indicator at 100mm to assist in the safe presentation of food
- Accepts GN1/1 gastronorm containers up to 100mm deep
- Completely removable well giving easy access for cleaning and maintenance
- Microprocessor controlled with automatic defrost & condense handling system
- 1.5mm stainless steel tops with radius front & rear
- Rear operator's side finished in stainless steel with radius corners
- Stainless steel interior with radius rear corners
- Four x 100mm swivel castors two braked

EXTRAS

- Gantries
- Tray slides
- Kick-plinths
- Push bar
- Choice of colour finish
- Height adjustable feet instead of castors

REFRIGERANT

R452a - zero ODP and low GWP refrigerant

OPERATING CONDITIONS

Designed to comply with the operating requirements of EN ISO 23953 - 2:2005

Performance level M1 (-1°C to +5°C) in Climate class 3 (25°C 60% RH 0.2m/s)

In use Victor refrigerated blown air delis will maintain the core product temperature of pre-chilled food below 5°C in ambient temperatures up to 27°C - 50% Relative Humidity



VICTOR

TELEPHONE
01274 722125

EMAIL
sales@victormfg.co.uk

WEBSITE
www.victoronline.co.uk