

SYNERGY DROP INS

REFRIGERATED HIGH DELI DISPLAY

MODEL NO: DRDH

The Synergy range of Refrigerated blown air high delis are designed to be dropped into a counter surface to form a food servery. Two sizes in the range which accept 100mm deep GN1/1 size gastronorm containers. Each Synergy display is self-contained and easily installed.



DIMENSIONS

DRDH3: 1177mm x 755mm x 710mm

DRDH4: 1504mm x 755mm x 710mm

ELECTRICAL CONNECTIONS

220V/240V; 1 phase 50Hz

DRDH3: 1.6kW loading

DRDH4: 2.1kW loading

Cable: 2 metres with 13 amp plug fitted

CONSTRUCTION

Top: Stainless steel

Exterior: Stainless steel

Interior: Stainless steel

CAPACITY

DRDH3: 3 x GN1/1

DRDH4: 4 x GN1/1

REFRIGERANT

R452a - zero ODP and low GWP refrigerant

OPERATING CONDITIONS

Designed to comply with the operating requirements of EN ISO 23953 - 2:2005

Performance level M1 (-1°C to +5°C) in

Climate class 3 (25°C 60% RH 0.2m/s)

In use Victor refrigerated Synergy units will maintain the core product temperature of pre-chilled food below 5°C in ambient temperatures up to 27°C - 50% Relative humidity

PRODUCT FEATURES

- Designed for assisted service, with rear preparation shelf

GANTRY FEATURES

- Constructed from 50mm diameter bright polished stainless steel tube
- Fluorescent illumination to stainless steel light box
- Toughened glass curved front screen and over shelf hinged for easy cleaning
- Glass side cheeks
- Two ambient glass mid-shelf
- Digital temperature control and readout

WELL FEATURES

- 304 Stainless steel well - 170mm deep
- Load line indicator at 100mm to assist in the safe presentation of food
- Accepts GN1/1 gastronorm containers up to 100mm deep
- Completely removable well giving easy access for cleaning and maintenance

OPTIONS

- Polyethylene cutting board
600 x 250 x 40mm - Fits over rear preparation shelf



VICTOR

TELEPHONE
01274 722125

EMAIL
sales@victormfg.co.uk

WEBSITE
www.victoronline.co.uk