SYNERGY DROP INS

REFRIGERATED DELI DISPLAY

MODEL NO: DRDL

The Synergy range of Refrigerated blown air delis are designed to be dropped into a counter surface to form a food servery. Three sizes in the range which accept 100mm deep GN1/1 size gastronorm containers. Each Synergy display is self-contained and easily installed.



DIMENSIONS

DRDL2: 850mm x 755mm x 540mm DRDL3: 1177mm x 755mm x 540mm DRDL4: 1504mm x 755mm x 540mm

ELECTRICAL CONNECTIONS

220V/240V; 1 phase 50Hz DRDL2: 1.6kW loading DRDL3: 1.6kW loading DRDL4: 2.1kW loading

Cable: 2 metres with 13 amp plug fitted

CONSTRUCTION

Top: Stainless steel Exterior: Stainless steel Interior: Stainless steel

CAPACITY

DRDL2: 2 x GN1/1

Available from stock for next day delivery DRDL3: 3 x GN1/1

Available from stock for next day delivery

DRDL4: 4 x GN1/1

REFRIGERANT

R452a - zero ODP and low GWP refrigerant

OPERATING CONDITIONS

Designed to comply with the operating requirements of EN ISO 23953 - 2:2005 Performance level M1 (-1°C to +5°C) in Climate class 3 (25°C 60% RH 0.2m/s) In use Victor refrigerated Synergy units will maintain the core product temperature of pre-chilled food below 5°C in ambient temperatures up to 27°C - 50% Relative Humidity

PRODUCT FEATURES

· Designed for assisted service, with rear preparation shelf

GANTRY FEATURES

- · Constructed from 50mm diameter bright polished stainless steel tube
- Fluorescent illumination to stainless steel light box
- · Toughened glass curved front screen and over shelf hinged for easy cleaning
- · Glass side cheeks
- · One ambient glass mid-shelf
- Digital temperature control and readout

WELL FEATURES

- 304 Stainless steel well 170mm deep
- Load line indicator at 100mm to assist in the safe presentation of food
- Accepts GN1/1 gastronorm containers up to 100mm deep
- Completely removable well giving easy access for cleaning and maintenance

· Polyethylene cutting board 600 x 250 x 40mm - Fits over rear preparation shelf





sales@victormfg.co.uk /