

SYNERGY DROP INS

REFRIGERATED MULTI-TIER 2 SHELF

MODEL NO: DRMT

The Synergy range of Refrigerated blown air multi-tiers are designed to be dropped into a counter surface to form a food servery. Four sizes in the range rear opening door or solid back models. Each Synergy display is self-contained and easily installed.



DIMENSIONS

DRMT22: 850mm x 660mm x 540mm
DRMT23: 1177mm x 660mm x 540mm
DRMT24: 1504mm x 660mm x 540mm
DRMT25: 1831mm x 660mm x 540mm

ELECTRICAL CONNECTIONS

220V/240V; 1 phase 50Hz
DRMT22: 2.1kW loading
DRMT23: 2.6kW loading
DRMT24: 3.01kW loading
DRMT25: 3.4kW loading
Cable: 2 metres with 13 amp plug fitted

CONSTRUCTION

Top: Stainless steel
Exterior: Stainless steel
Interior: Stainless steel

CAPACITY

DRDD2: 2 x GN1/1
DRDD3: 3 x GN1/1
DRDD4: 4 x GN1/1
DRDD5: 5 x GN1/1

REFRIGERANT

R452a - zero ODP and low GWP refrigerant

OPERATING CONDITIONS

Designed to comply with the operating requirements of EN ISO 23953 - 2:2005
Performance level M1 (-1°C to +5°C) in
Climate class 3 (25°C 60% RH 0.2m/s)
In use Victor refrigerated Synergy units will maintain the core product temperature of pre-chilled food below 5°C in ambient temperatures up to 27°C - 50% Relative Humidity

PRODUCT FEATURES

- A refrigerated cabinet that maintains the temperature of pre-chilled food held in the well or on the shelves
- Designed for self service

GANTRY FEATURES

- Constructed from 50mm diameter bright polished stainless steel tube
- Fluorescent illumination to stainless steel light box
- Toughened glass screen and side cheeks
- Digital temperature control and readout
- Two height adjustable glass shelves

WELL FEATURES

- 304 Stainless steel well - 170mm deep to accommodate drinks bottles under lower shelf
- Completely removable well giving easy access for cleaning and maintenance

OPTIONS

- Solid back versions instead of rear doors for positioning against walls
- Shelf edge ticket strips



VICTOR

TELEPHONE
01274 722125

EMAIL
sales@victormfg.co.uk

WEBSITE
www.victoronline.co.uk