MODULAR COUNTERS

JAMAICAN REFRIGERATED **BLOWN AIR WELLS**

MODEL NO: JBA

GN1/1 gastronorm compatible blown air refrigerated mobile salad well. Ideal for general purpose usage in all catering establishments, schools & colleges, residential care homes, pubs, hotels and cafes.



DIMENSIONS

JBA30: 1205mm x 670mm x 900mm Well: 975mm x 530mm x 170mm JBA40: 1535mm x 670mm x 900mm Well: 1305mm 530mm x 170mm JBA50: 1860mm x 670mm x 900mm Well: 1635mm x 530mm x 170mm Standard counter top height is 900mm, JBA30 units can be manufactured with at a reduce height of 850 or 875mm if required

ELECTRICAL CONNECTIONS

220V/240V; 1 phase 50Hz 1205 model: 1.6kW loading 1535 model: 2.1kW loading 1860 model: 2.4kW loading

CONSTRUCTION

Top: Stainless steel

Exterior: Colour plastic coated steel or

stainless steel

Interior: Stainless steel

CAPACITY

1205 model: 3 x GN1/1 x 100mm deep 1606 model: 4 x GN1/1 x 100mm deep 1906 model: 5 x GN1/1 x 100mm deep

REFRIGERANT

R452a - zero ODP and low GWP refrigerant

OPERATING CONDITIONS

Designed to comply with the operating requirements of EN ISO 23953 - 2:2005. Performance level M1 (-1°C to + 5°C) in Climate class 3 (25°C 60% RH 0.2m/s). In use these units will maintain the core product temperature of pre-chilled food below 5°C in ambient temperatures up to 27°C - 50% Relative humidity

PRODUCT FEATURES

- 304 grade stainless steel well 170mm
- Load line indicator at 100mm to assist in the safe presentation of food
- Accepts GN1/1 gastronorm containers up to 100mm deep
- · Completely removable well giving easy access for cleaning and maintenance
- · Microprocessor controlled with automatic defrost & condense handling system
- Rear operator's side finished in stainless
- Open ambient cupboard to rear 1535 & 1855mm units only
- Four x 100mm swivel castors two braked

EXTRAS

- Gantries
- · Tray slides
- · Kick-plinths
- · Push bars
- Corner bumpers
- · Drop down end shelf
- · Choice of colour finish





sales@victormfg.co.uk /