

MODULAR COUNTERS

JAMAICAN REFRIGERATED BLOWN AIR ISLAND WELLS

MODEL NO: JBAI

GN1/1 gastronorm compatible blown air island refrigerated mobile salad well. Ideal for general purpose usage in all catering establishments, schools & colleges, residential care homes, pubs, hotels and cafes. Paneled to 4 sides for all round service.



DIMENSIONS

JBAI30: 1205mm x 670mm x 900mm

Well: 975mm x 530mm x 170mm

JBAI40: 1535mm x 670mm x 900mm

Well: 1305mm x 530mm x 170mm

JBAI50: 1860mm x 670mm x 900mm

Well: 1635mm x 530mm x 170mm

ELECTRICAL CONNECTIONS

220V/240V; 1 phase 50Hz

1205 model: 1.6kW loading

1535 model: 2.1kW loading

1860 model: 2.4kW loading

CONSTRUCTION

Top: Stainless steel

Exterior: Colour plastic coated steel or stainless steel

Interior: Stainless steel

CAPACITY

1205 model: 3 x GN1/1 x 100mm deep

1535 model: 4 x GN1/1 x 100mm deep

1860 model: 5 x GN1/1 x 100mm deep

REFRIGERANT

R452a - zero ODP and low GWP refrigerant

OPERATING CONDITIONS

Designed to comply with the operating requirements of EN ISO 23953 - 2:2005

Performance level M1 (-1°C to +5°C) in Climate class 3 (25°C 60% RH 0.2m/s)

In use these units will maintain the core product temperature of pre-chilled food below 5°C in ambient temperatures up to 27°C - 50% Relative humidity

PRODUCT FEATURES

- 304 grade stainless steel well - 170mm deep
- Load line indicator at 100mm to assist in the safe presentation of food
- Accepts GN1/1 gastronorm containers up to 100mm deep
- Completely removable well giving easy access for cleaning and maintenance
- Microprocessor controlled with automatic defrost & condense handling system
- Paneled to 4 sides for all round service
- Four x 100mm swivel castors two braked

EXTRAS

- Gantries
- Tray slides
- Kick-plinths
- Push bars
- Corner bumpers
- Drop down end shelf
- Choice of colour finish
- Height adjustable feet instead of castors



TELEPHONE
01274 722125

EMAIL
sales@victormfg.co.uk

WEBSITE
www.victoronline.co.uk