

## HOT CUPBOARDS

## REFRIGERATED SALAD WELL

### MODEL NO: RW40MS

GN1/1 gastronorm compatible blown air refrigerated mobile salad well. Ideal for general purpose usage in all catering establishments, schools & colleges, residential care homes, pubs, hotels and cafes.



#### DIMENSIONS

External: 1535mm x 650mm x 900mm  
Well: 1305mm x 530mm x 170mm

#### ELECTRICAL CONNECTIONS

220V/240V; 1 phase 50Hz, 2.1kW loading,  
Cable: 2 metres with 13 amp plug fitted

#### REFRIGERANT

R452a - zero ODP and low GWP refrigerant

#### CONSTRUCTION

Top: Stainless steel  
Exterior: Stainless steel  
Interior: Stainless steel

#### CAPACITY

4 x GN1/1 x 100mm deep

#### OPERATING CONDITIONS

Designed to comply with the operating requirements of EN ISO 23953 - 2:2005.  
Performance level M1 (-1°C to +5°C) in Climate class 3 (25°C 60% RH 0.2m/s).  
In use these units will maintain the core product temperature of pre-chilled food below 5°C in ambient temperatures up to 27°C - 50% Relative Humidity

#### PRODUCT FEATURES

- 304 grade stainless steel well - 170mm deep
- Load line indicator at 100mm to assist in the safe presentation of food
- Accepts GN1/1 gastronorm containers up to 100mm deep
- Completely removable well giving easy access for cleaning and maintenance
- Microprocessor controlled with automatic defrost & condense handling system
- Rear operator's side finished in stainless steel
- Open ambient cupboard to rear - 1535mm
- Four x 100mm swivel castors two braked

#### EXTRAS

- Tray slides
- Push bars
- Corner bumpers
- Height adjustable feet in place of castors



# VICTOR

TELEPHONE  
01274 722125

EMAIL  
sales@victormfg.co.uk

WEBSITE  
www.victoronline.co.uk