SYNERGY DROP INS

SQ REFRIGERATED MULTI-TIER 3 SHELF

MODEL NO: SSRMT

The Synergy range of Refrigerated blown air multi-tiers are designed to be dropped into a counter surface to form a food servery. Four sizes in the range rear opening door or solid back models. Each Synergy display is selfcontained and easily installed.



DIMENSIONS

SSRMT2: 850mm x 660mm x 710mm SSRMT3: 1177mm x 660mm x 710mm SSRMT4: 1504mm x 660mm x 710mm SSRMT5: 1831mm x 660mm x 710mm

ELECTRICAL CONNECTIONS

SSRMT5 fitted with 16 amp plug

220V/240V; 1 phase 50Hz SSRMT2: 2.1kW loading SSRMT3: 2.6kW loading SSRMT4: 3.0kW loading SSRMT5: 3.4kW loading Cable: Units under 3.1kW fitted with 2 metres of cable and 13amp plug

CONSTRUCTION

Top: Stainless steel Exterior: Stainless steel Interior: Stainless steel

CAPACITY

REAR OPENING DOORS

SSRMT2: 2 x GN1/1 SSRMT3: 3 x GN1/1 SSRMT4: 4 x GN1/1 SSRMT5: 5 x GN1/1

SOLID BACK WALL

SSRMT2W: 2 x GN1/1 SSRMT3W: 3 x GN1/1 SSRMT4W: 4 x GN1/1 SSRMT5W: 5 x GN1/1

REFRIGERANT

R452a - zero ODP and low GWP refrigerant

OPERATING CONDITIONS

Designed to comply with the operating requirements of EN ISO 23953 - 2:2005 Performance level M1 (-1°C to + 5°C) in Climate class 3 (25°C 60% RH 0.2m/s)

PRODUCT FEATURES

- · A refrigerated cabinet that maintains the temperature of pre-chilled food held in the well or on the shelves
- · Designed for self service

GANTRY

- · Constructed from bright polished stainless
- LED illumination to stainless steel light box
- · Toughened glass top and side cheeks
- Digital temperature control and readout
- Two height adjustable glass shelves

WELL

- 304 Stainless steel well 170mm deep to accommodate drinks bottles under lower shelf
- · Completely removable well giving easy access for cleaning and maintenance

OPTIONS

- · Solid back versions instead of rear doors for positioning against walls
- Shelf edge ticket strips





sales@victormfg.co.uk /