SYNERGY DROP INS

SQ REFRIGERATED MULTI-TIER 2 SHELF
MODEL NO: SSRMT

The Synergy range of Refrigerated blown air high delis are designed to be dropped into a counter surface to form a food servery. Four sizes in the range which accept 100mm deep GN1/1 size gastronorm containers. Each Synergy display is self-contained and easily installed.

DIMENSIONS
SSRMT22: 850mm x 660mm x 710mm
SSRMT23: 1177mm x 660mm x 710mm
SSRMT24: 1504mm x 660mm x 710mm
SSRMT25: 1831mm x 660mm x 710mm

ELECTRICAL CONNECTIONS
220V/240V; 1 phase 50Hz
SSRMT22: 2.1kW loading
SSRMT23: 2.6kW loading
SSRMT24: 3.0kW loading
SSRMT25: 3.4kW loading
Cable: Units under 3.1kW fitted with 2 metres of cable and 13amp plug
SSRMT25 fitted with 16 amp plug

CONSTRUCTION
Top: Stainless steel
Exterior: Stainless steel
Interior: Stainless steel

CAPACITY
REAR OPENING DOORS
SSRMT22: 2 x GN1/1
SSRMT23: 3 x GN1/1
SSRMT24: 4 x GN1/1
SSRMT25: 5 x GN1/1

SOLID BACK WALL
SSRMT22W: 2 x GN1/1
SSRMT23W: 3 x GN1/1
SSRMT24W: 4 x GN1/1
SSRMT25W: 5 x GN1/1

REFRIGERANT
R452a - zero ODP and low GWP refrigerant

OPERATING CONDITIONS
Designed to comply with the operating requirements of EN ISO 23953 - 2:2005 Performance level M1 (-1°C to + 5°C) in Climate class 3 (25°C 60% RH 0.2m/s)

PRODUCT FEATURES
• A refrigerated cabinet that maintains the temperature of pre-chilled food held in the well or on the shelves
• Designed for self service

GANTRY
• Constructed from bright polished stainless steel
• LED illumination to stainless steel light box
• Toughened glass top and side cheeks
• Digital temperature control and readout
• Two height adjustable glass shelves

WELL
• 304 Stainless steel well - 170mm deep to accommodate drinks bottles under lower shelf
• Completely removable well giving easy access for cleaning and maintenance

OPTIONS
• Solid back versions instead of rear doors for positioning against walls
• Shelf edge ticket strips