

## SYNERGY DROP INS

### SQ REFRIGERATED BLOWN AIR WELL

#### MODEL NO: SSRWL

The Synergy range of Refrigerated blown air wells are designed to be dropped into a counter surface to form a food servery. Four sizes in the range which accept 100mm deep GN1/1 size gastronorm containers. Each Synergy display is self-contained and easily installed.



#### DIMENSIONS

SSRWL2: 850mm x 660mm x 540mm  
SSRWL3: 1177mm x 660mm x 540mm  
SSRWL4: 1504mm x 660mm x 540mm  
SSRWL5: 1831mm x 660mm x 540mm

#### ELECTRICAL CONNECTIONS

220V/240V; 1 phase 50Hz  
SSRWL2: 1.6kW loading  
SSRWL3: 1.6kW loading  
SSRWL4: 2.1kW loading  
SSRWL5: 2.4kW loading  
Cable: Units under 3.1kW fitted with 2 metres of cable and 13amp plug

#### CONSTRUCTION

Top: Stainless steel  
Exterior: Stainless steel  
Interior: Stainless steel

#### CAPACITY

SSRWL2: 2 x GN1/1  
SSRWL3: 3 x GN1/1  
SSRWL4: 4 x GN1/1  
SSRWL5: 5 x GN1/1

#### REFRIGERANT

R452a - zero ODP and low GWP refrigerant

#### OPERATING CONDITIONS

Designed to comply with the operating requirements of EN ISO 23953 - 2:2005  
Performance level M1 (-1°C to + 5°C) in Climate class 3 (25°C 60% RH 0.2m/s)  
In use Victor refrigerated Synergy units will maintain the core product temperature of pre-chilled food below 5°C in ambient temperatures up to 27°C - 50% Relative Humidity

#### PRODUCT FEATURES

- Designed for self or assisted service

#### GANTRY

- Constructed from bright polished stainless steel
- LED illumination to stainless steel light box
- Toughened glass screen and over shelf
- Digital temperature control and readout

#### WELL

- 304 Stainless steel well - 170mm deep
- Load line indicator at 100mm to assist in the safe presentation of food
- Accepts GN1/1 gastronorm containers up to 100mm deep
- Completely removable well giving easy access for cleaning and maintenance

#### OPTIONS

- Front facing controls



TELEPHONE  
01274 722125

EMAIL  
sales@victormfg.co.uk

WEBSITE  
www.victoronline.co.uk