

SYNERGY DROP INS

REFRIGERATED WELL

MODEL NO: WDRWL

The Synergy range of Heated Refrigerated and Ambient displays designed to be dropped into a counter surface to form a food servery. Each Synergy display is self-contained and easily installed. Synergy displays complement each other in both style and profile. They are constructed using satin finish stainless steel surrounds.



DIMENSIONS

WDRWL2: 850mm x 660mm x 20mm
WDRWL3: 1177mm x 660mm x 20mm
WDRWL4: 1504mm x 660mm x 20mm
WDRWL5: 1831mm x 660mm x 20mm

ELECTRICAL CONNECTIONS

220V/240V; 1 phase 50Hz
WDRWL2: 1.6kW loading
WDRWL3: 1.6kW loading
WDRWL4: 2.1kW loading
WDRWL5: 2.4kW loading
Cable: fitted 2 metres of cable and 13 amp plug

CONSTRUCTION

Top: Stainless steel
Exterior: Stainless steel
Interior: Stainless steel

CAPACITY

WDRWL2: 2 x GN1/1
WDRWL3: 3 x GN1/1
WDRWL4: 4 x GN1/1
WDRWL5: 5 x GN1/1

REFRIGERANT

R452a - zero ODP and low GWP refrigerant

OPERATING CONDITIONS

Designed to comply with the operating requirements of EN ISO 23953 - 2:2005 Performance level M1 (-1°C to + 5°C) in Climate class 3 (25°C 60% RH 0.2m/s)
In use Victor refrigerated Synergy units will maintain the core product temperature of pre-chilled food below 5°C in ambient temperatures up to 27°C
- 50% Relative Humidity

PRODUCT FEATURES

- Designed for self or assisted service
- Digital temperature control and readout.
- 304 Stainless steel well - 170mm deep
- Load line indicator at 100mm to assist in the safe presentation of food
- Accepts GN1/1 gastronorm containers up to 100mm deep
- Completely removable well giving easy access for cleaning and maintenance



VICTOR

TELEPHONE
01274 722125

EMAIL
sales@victormfg.co.uk

WEBSITE
www.victoronline.co.uk